

XB13 Repair Parts

Part Number	Description	4TTB3018H1000AA	4TTB3024H1000AA	4TTB3060D1000DA
COL16420	COIL; CONDENSER SPINE-FIN			X
COL24030	COIL; CONDENSER SPINE-FIN	X	X	
COM10057	COMPRESSOR; SCROLL, ALLIANCE, SXA020C1BPZ, 1.66 TON, 208-230/60/1, R410A, RED		X	
COM10511	COMPRESSOR; SCROLL, ALLIANCE, SXA016C1BPZ, 1.30 TON, 208/230/60/1, R410A, RED	X		
COM10917	COMPRESSOR; SCROLL, 208/230/60/1, 4.5 TONS, R410A. INCLUDES WIRE HARNESS, DOME TEMPERATURE SWITCH, TERMINAL COVER AND GASKET			X
CPT00120	CAPACITOR; RUN, 7.5 MFD, 370V, OVAL, W/O RESISTOR			X
CPT00659	CAPACITOR; DUAL, 30/5 MFD, 440V, ROUND, W/O RESISTOR	X	X	
CPT01074	CAPACITOR; RUN, 80 MFD, 440V, ROUND, W/O RESISTOR			X
CTR02574	CONTACTOR; 1P 40A 24VAC / SCREWS	X	X	
CTR02576	CONTACTOR; 2P 40A 24VAC / SCREWS			X
DHY01457	DRIER; LIQUID LINE; SERVICE FIRST; 5 CU. IN.; 5.4 TON CAPACITY; 3/8" ODF INLET X 3/8" ODF OUTLET; APPROVED FOR MINERAL OIL AND POE OIL REFRIGERANTS	X	X	X
FAN04074	FAN; 3 BLADE, ALUMINUM, 27.6 IN DIA, 19 DEG PITCH, 0.50 IN BORE, CCW, 1 SET SCREW-STEEL, SPIDER 0.054 THK, FINISH/PAINT			X
FAN04635	FAN; 2 SWEPT BLADES, 18.92 IN DIA, 28 DEG PITCH, 0.50 IN BORE, CCW, ALUMINUM, 1 SET SCREW-STEEL, SPIDER 0.050 THK	X	X	
MOT11447	MOTOR; 1/8 HP, 200/230/60/50/1, 1075 RPM, 48 FRAME PSC, SLEEVE BEARINGS, CCW, 5 MFD @ 370V (MOTOR INCLUDES SCREW SCR01989 QTY 4).	X	X	
MOT16278	MOTOR; 1/5 HP, 200/230/60/1, 850 RPM, 48 FRAME, PSC, BALL BEARING, CCW, 7.5 MFD CPT AT 370V			X
PLU01186	PLUG; SCROLL COMPRESSOR	X	X	

XB13 Repair Parts

Part Number	Description	4TTB3018H1000AA	4TTB3024H1000AA	4TTB3060D1000DA
SWT03273	SWITCH; HIGH PRESSURE, SPST, OPEN @ 650 PSIG, CLOSE @ 500 PSIG, 88" YELLOW LEAD			X
SWT03274	SWITCH; HIGH PRESSURE, SPST, OPEN @ 650 PSIG, CLOSE @ 500 PSIG, 75" YELLOW LEAD	X	X	
SWT03347	SWITCH; LOW PRESSURE, OPEN @ 50 PSIG CLOSE @ 70 PSIG			X
SWT03374	SWITCH; LOW PRESSURE, OPEN @ 50 PSIG CLOSE @ 70 PSIG	X	X	
THT03092	THERMOSTAT; COMPRESSOR DOME TEMPERATURE SWITCH, OPENS AT 239-257F, CLOSSES AT 151-187F, WIRE LENGTH 85 INCH.			X
VAL07326	VALVE, SERVICE GAS, 0.63 OD X 0.63 OD, BALL VALVE ASSY, BRASS, FEMALE BRAZE TO FEMALE BRAZE, LEFT HAND SERVICE PORT	X	X	
VAL07328	VALVE, SERVICE GAS, 0.88 OD X 0.88 OD, BALL VALVE ASSY, BRASS, FEMALE BRAZE TO FEMALE BRAZE, LEFT HAND SERVICE PORT			X
VAL09292	VALVE; SERVICE LIQUID, 0.31 ODF X 0.38 ODF	X	X	
VAL09293	VALVE; SERVICE LIQUID, 0.38 OD X 0.38 OD, VALVE ASSY			X
WIR07307	WIRE; HARNESS, WIRE LENGTH 73 INCH. ALSO INCLUDES TERMINAL COVER AND GASKET			X