

XV20I Repair Parts

Part Number	Description	4TTV0024 A1000AA	4TTV0036 A1000AA	4TTV0048A 1000AA	4TTV0060 A1000AA
CNT07026	CONTROL; DISPLAY ASSEMBLY	X	X	X	X
COL21417	COIL; SPINE FIN	X			
COL21419	COIL; SPINE FIN		X		
COL21420	COIL; SPINE FIN			X	
COL21424	COIL; SPINE FIN				X
COM10829	COMPRESSOR; SCROLL, RPA028A1CPA, 2.3 TON, 208V/60/1, R-410A, 3/4 SUCTION, 1/2 DISCHARGE, STUB TUBE	X	X		
COM10830	COMPRESSOR; SCROLL, RPA035A1CPA, 2.9 TON, 208V/60/1, R-410A, 3/4 SUCTION, 1/2 DISCHARGE, STUB TUBE			X	
COM10831	COMPRESSOR; SCROLL, RPA044A1CPA, 3.6 TON, 208V/60/1, R-410A, 3/4 SUCTION, 1/2 DISCHARGE, STUB TUBE				X
DHY01452	DRIER; BI-FLOW; SERVICE FIRST; 16 CU. IN; DCB163S, 3/8 ODF CONNECTIONS; 5.7 TON CAPACITY; APPROVED FOR MINERAL OIL AND POE OIL REFRIGERANTS	X	X	X	X
DRV01788	DRIVE; VARIABLE SPEED	X	X	X	X
FAN03657	FAN, 2 SWEPT BLADE, 23 IN DIA, 24.5 DEG PITCH, 0.50 IN BORE, CCW, ALUMINUM	X	X		
FAN04368	FAN, 3 SWEPT BLADE, 27.5 IN DIA, 26 DEG PITCH, 0.50 IN BORE, CCW, ALUMINUM			X	X
MOD01574	MODULE; PERSONALITY	X	X	X	X
MOT16195	MOTOR; 1/3 HP, TWO SPEED, 200-240/60/1, 200-1200 RPM, 48 FRAME, ECM	X	X		
MOT16196	MOTOR; 1/3 HP, TWO SPEED, 200-240/60/1, 200-1200 RPM, 48 FRAME, ECM			X	X
SEN02136	SENSOR; DOME, NTC THERMISTOR, TEMP RANGE -40C TO 150C, 1.69 L WITH MOLEX CONNECTOR AND 80 IN LEADS	X	X	X	X
SEN02203	SENSOR; ASSEMBLY, AMBIENT, 2 PIN CONNECTOR, 36 IN LENGTH	X	X	X	X
SEN02207	SENSOR; SUCTION LINE, 0.750 DIA TUBE, 2 PIN CONNECTOR, 43 IN ORANGE LEADS	X	X		
SEN02208	SENSOR; SUCTION LINE, 0.875 DIA TUBE, 2 PIN CONNECTOR, 47 IN ORANGE LEADS			X	X
SWT03749	SWITCH; HIGH PRESSURE, SPST, OPEN AT 650 PSIG, CLOSE AT 500 PSIG, 83 INCH QC LEADS, BRAZED	X	X	X	X

XV20I Repair Parts

Part Number	Description	4TTV0024 A1000AA	4TTV0036 A1000AA	4TTV0048A 1000AA	4TTV0060 A1000AA
TDR00645	TRANSDUCER; PRESSURE, SUCTION, 0.5 VDC AT 14.7 PSIA, 4.5 VDC AT 400 PSIA, 1/4" SAE FEMALE FLARE WITH DEFLATOR, 7/16-20 UNF-2B 5/8 ACROSS FLATS, 72 IN LEADS	X	X	X	X
VAL07327	VALVE, SERVICE GAS, 0.75 OD X 0.75 OD, BALL VALVE ASSY, BRASS, FEMALE BRAZE TO FEMALE BRAZE, LEFT HAND SERVICE PORT		X		
VAL07328	VALVE, SERVICE GAS, 0.88 OD X 0.88 OD, BALL VALVE ASSY, BRASS, FEMALE BRAZE TO FEMALE BRAZE, LEFT HAND SERVICE PORT			X	X
VAL07343	VALVE, SERVICE GAS, 0.63 OD X 0.75 OD, BALL VALVE ASSY, BRASS, FEMALE BRAZE TO FEMALE BRAZE, LEFT HAND SERVICE PORT	X			
VAL09293	VALVE, SERVICE LIQUID, 0.38 OD X 0.38 OD, VALVE ASSY	X	X	X	X
WIR07134	WIRE; HARNESS, CONTROL DISPLAY ASSEMBLY, (2) 4 PIN CONNECTORS, RED-GRN-WHT-BLK WIRES	X	X	X	X
WIR07181	WIRE; HARNESS-SENSOR JUNCTION, 18 PIN DRIVE BULKHEAD CONNECTOR, INCLUDES CONNECTORS FOR THESE SENSORS: SUCTION PRESSURE, AMBIENT, SUCTION TEMP, COIL SENSOR, DOME TEMP SENSOR	X	X	X	X
WIR07182	WIRE; HARNESS-CL-2 FIELD, BLU, RED, BRN WIRES, 3 PIN CONNECTOR, 54 IN LENGTH	X	X	X	X
WIR07183	WIRE; HARNESS-POWER HV, BLK/BLU, BRN/RED WIRES, 2 PIN MOLEX PLUG, 36 IN LENGTH	X	X	X	X
WIR07184	WIRE; HARNESS, COMPRESSOR SHIELD ASSEMBLY, MOLDED PLUG, 12 AWG, 50 INCH LENGTH	X	X	X	
WIR07185	WIRE; HARNESS, COMPRESSOR SHIELD ASSEMBLY, MOLDED PLUG, 10 AWG, 54 INCH LENGTH				X